

**FAA APPROVED
R44 II PILOT'S OPERATING HANDBOOK
CANADIAN SUPPLEMENT**

This supplement must be included in the FAA-approved Robinson R44 II Pilot's Operating Handbook for Canadian-registered aircraft.

The information contained herein supplements or supersedes the basic manual only in those areas listed in this supplement. For limitations, procedures, and performance information not contained in this supplement, consult the basic R44 II Pilot's Operating Handbook.


This supplement is approved by the United States Federal Aviation Administration on behalf of Transport Canada.

APPROVED BY: 
Manager, Flight Test Branch, ANM-160L
Federal Aviation Administration, LAACO
Transport Airplane Directorate

DATE: May 28, 2003

LOG OF REVISIONS

Page No.	Date	Page No.	Date
1	21 Oct 11		
2	28 May 03		
3	21 Oct 11		

REVISIONS
APPROVED BY: 
Manager, Flight Test Branch, ANM-160L
Federal Aviation Administration, LAACO
Transport Airplane Directorate

DATE: October 21, 2011

LIMITATIONS

Ambient temperature limits for operation are -40°C to +39°C.

At temperatures below -5°C, the Cold Weather Procedures given below must be followed.

COLD WEATHER PROCEDURES

Special precautions should be taken if the helicopter is to be started after a cold soak in ambient temperatures below -5°C. Ensure that the correct engine oil grade is used (Refer to Section 8 in the main body of this manual). Preheat the engine oil, engine compartment and main rotor gearbox compartment to a minimum temperature of approximately -5°C. (Pilot judgment may be used to estimate this temperature.) Preheating may be achieved by using a combination of an approved electric engine preheat system, portable heaters, and insulating covers. Use caution not to damage any equipment/wiring with excessive direct heat.

CAUTION

Failure to preheat engine before starting may result in internal engine damage.

When landing at ambient temperatures below -5°C in areas without preheating equipment, start the helicopter hourly and run-up to normal operating temperatures. More frequent starts may be required at colder temperatures. Be sure to run the helicopter long enough to recharge the battery after each start.

PLACARDS

Near main fuel tank filler cap on tanks with capacity marked in gallons:

USABLE CAP. 116 LITRES

Near aux fuel tank filler cap on tanks with capacity marked in gallons:

USABLE CAP. 69 LITRES

NOTE

Fuel tanks with bladders do not have a capacity marking. See Limitations section in basic manual for fuel capacities of tanks with and without bladders.

INTENTIONALLY BLANK